

Threadlocker



Dynatex®

Product Solution

Thread Sealant w/ PTFE

Sealants



Anti-Seize



Gasket
Makers



Aerosols



Dynatex Thread Sealant w/ PTFE is an all purpose thread sealant that remains pliable after installation. Can be used on all threaded joints in plastic, aluminum, monel, or stainless steel lines against water, natural gas, LPG, gasoline and others. Temperature range -35°F - +550°F

- Non Drip Formula
- Non – Hardening
- Non – Toxic
- Good Heat Resistance
- Contains PTFE
- Resists Corrosion

Dynatex is an ISO 9001 certified manufacturer and packager of branded and private label chemicals for everyday Automotive, Heavy Duty and Industrial Maintenance Markets

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case	Loctite® Functional Equivalent
49494	Thread Selant w/ PTFE 4oz. Brush Top Bottle	12	37545
49495	Thread Selant w/ PTFE 16oz. Brush Top Bottle	6	37547

Dynatex®

Dynatex

350 Ring Road • Elizabethtown, KY 42701
(800) 999-2937 • Fax (270) 769-6418
Outside U.S. +1(270) 769-5557 • Fax +1(270) 769-6418
Email sales@dynatexinc.com
www.dynatexinc.com

Accumetric Asia Pacific, LTD

18 Kitpanit Bldg. 5th Floor
#502 Patpong Road • Suriyawong, Bangrak
Bangkok, 10500 Thailand
(662) 634-3060 • Fax (662) 634-3066

To discontinue receiving these notifications, please contact us at opt-out@dynatexinc.com